

# PEOPLES STEEL MILLS LIMITED

Manghopir, Karachi.

## REQUEST FOR QUOTATION



M/s.

RFQ NO. PSM/LP-22/PR-24060/24338

ISSUED ON 12-MAY-25

DUE ON 27-MAY-25

Dear Sirs,

We invite you to quote for the following material on F.O.R PSM site basis inclusive of all Government taxes and levies on the terms and conditions attached herewith valid for 45 days. Your offer must reach the office of the undersigned by the date mentioned above.

S. NO.	DESCRIPTION	QUANTITY	RATE
1	LOW VOLTAGE POWER CABLE.CONDUCTOR MATERIAL: COPPER.SIZE: 95MM(SQ).NO. OF CORE: 1CORE.VOLTAGE LEVEL: 600/1000VAC.CONDUCTOR TYPE: FLEXIBLE.CABLE SHAPE: CIRCULAR. PROTECTION: NON ARMOURED.INSULATION: RUBBER.OVER SHEATH: PVC	100 MTR	
2	LOW VOLTAGE POWER CABLE.CONDUCTOR MATERIAL: COPPER.SIZE: 2.5MM(SQ).NO. OF CORE: 2CORE.VOL LEVEL: 600/1000VAC.CONDUCTOR TYPE: FLEXIBLE.CABLE SHAPE: CIRCULAR. PROTECTION: NON ARMOURED.INSULATION: PVC.OVER SHEATH: PVC	500 MTR	
3	LOW VOLTAGE POWER CABLE.CONDUCTOR MATERIAL: COPPER.SIZE: 2.5MM(SQ).NO. OF CORE: 3CORE.VOLTAGE LEVEL: 600/1000VAC.CONDUCTOR TYPE: FLEXIBLE.CABLE SHAPE: CIRCULAR. PROTECTION: NON ARMOURED.INSULATION: PVC.OVER SHEATH: PVC	500 MTR	
4	LOW VOLTAGE POWER CABLE, CONDUCTOR MATERIAL: COPPER, SIZE: 16MM(SQ), NO OF CORE: 6 CORE, VOLTAGE LEVEL: 600/1000VAC, CONDUCTOR TYPE: FLEXIBLE, CABLE SHAPE: CIRCULAR, PROTECTION: NON ARMOURED, INSULATION: RUBBER, OVER SHEATH: RUBBER	100 MTR	
5	LOW VOLTAGE POWER CABLE, CONDUCTOR MATERIAL: COPPER, SIZE: 1.5MM(SQ), NO OF CORE: 3 CORE, VOLTAGE LEVEL: 600/1000VAC, CONDUCTOR TYPE: FLEXIBLE, CABLE SHAPE: CIRCULAR, PROTECTION: NON ARMOURED, INSULATION: PVC, OVER SHEATH: PVC	500 MTR	

**NOTE :** 1. Delivery lead time should be within 30 days after receipt of Order.  
2. Payment will be made within 45 days after acceptance of material.  
3. Offer must be sent to Attention of Head (Procurement) through Fax / Post / or Email: nauman@psmltd.com.

**Yours Sincerely**  
**for PEOPLES STEEL MILLS LIMITED**